

PowerLite® Pro Z8350WNL

MULTIMEDIA PROJECTOR



Powerful, widescreen, HD performance. Ultra-bright images.

A powerful performer that's easy to install, manage and maintain, the PowerLite Pro Z8350WNL multimedia projector offers 8500 lumens of color/white light output¹ for captivating presentations in virtually any venue, even those with ambient light. Featuring WXGA widescreen resolution, innovative 3LCD technology and a contrast ratio up to 5000:1, the Z8350WNL delivers brilliant images in lecture halls, conference centers and entertainment venues. Setup and installation are easy with 360-degree projection, edge blending and more. Offering diverse connectivity and a full suite of monitor and control features, this high-definition, high brightness projector ensures easy integration with complex devices, plus a low overall cost of ownership. Choose from a variety of optional lenses to meet most any need.

Ultra-bright, widescreen, HD performance — 8500 lumens color/white light output¹; WXGA (16:10) resolution

EPSON Projectors

Advanced features — edge blending, split screen and DICOM simulation mode² **Diverse connectivity for easy integration** — includes HDMI and LAN connectivity

PowerLite® Pro Z8350WNL

MULTIMEDIA PROJECTOR

The best-selling projectors in the world

Epson offers a wide range of high-quality projectors to meet most any need. Built with image quality and reliability in mind, EPSON® projectors enhance communication and inspire collaboration, while offering a low total cost of ownership. From ultraportable projectors designed for educational settings to boardroom-ready installable business projectors, Epson has the model made for you.



Image Quality


3LCD technology — for quality and color that's beyond amazing

Innovative technology with proven reliability

- 3 chips for full-time, vibrant color
- 25% less electricity required per lumen of brightness when compared to 1-chip DLP projectors³
- Over 20 years of road-tested reliability built into every projector







Amazing color and white light output

The PowerLite Pro Z8350WNL delivers 8500 lumens of color

light output and 8500 lumens of white light output¹ for true-to-life, vibrant, colorful images, even in ambient light. For today's colorrich, multimedia content, users



want a projector that delivers both optimum white and color imagery. That's why the industry has developed a new metric called Color Light Output.

Always look for Color Light Output when choosing a projector

- For optimum image quality and performance, the projector you choose should offer equal levels of color and white light output
- When the two measurements are not identical, images do not look balanced
- Whites may be brighter, making the colored areas look dull and flat
- The combination of color richness (color light output) and brightness (white light output) is as critical as the combination of bass and treble would be when purchasing audio equipment



High color light output

Low color light output

Better Products for a Better Future™

For more information on Epson's environmental programs, go to eco.epson.com



Eco Features

- · Energy-efficient 3LCD, 3-chip technology
- Epson America, Inc. is a SmartWaySM Transport Partner⁴

Brilliant widescreen performance

Featuring WXGA resolution (16:10), the PowerLite Pro Z8350WNL is ideal for use with the latest-generation widescreen computers and for projecting high-definition content. It gives you:

- 30% more image area than a 4:3 image
- 10% more image area than a 16:9 image

The PowerLite Pro Z8350WNL still allows you to display 4:3 and 16:9 content without losing image quality.

C²Fine[™] technology delivers blacker blacks

C²Fine technology offers smooth, uniform images with exceptional contrast for better image quality. Based on this new phase-compensation technology, light leakage is eliminated, allowing for the reproduction of blacker blacks. C²Fine technology is combined with an auto iris, which allows for a contrast ratio up to 5000:1.



With C²Fine



Without C²Fine

Enhanced Super-resolution technology for sharp, dramatically rich images

- Makes DVDs and standard- and high-definition content come alive via its mixed color separation techniques and imaging simulation
- Delivers crisp, clear images with super high-quality resolution
- Sharpens blurry images that have been enlarged by a general upscaling process





Super-resolution off

Super-resolution on

Award-winning Faroudja DCDi[®] Cinema for advanced video


The PowerLite Pro Z8350WNL features a Faroudja DCDi Cinema chipset, a video enhancement technology that produces exceptional image quality without introducing artifacts. Faroudja DCDi (Directional Correlational Deinterlacing) was developed to eliminate jagging, using a unique algorithm. This technology, in combination with decoding, deinterlacing and enhancement technologies, won an Emmy Award from the National Academy of Television Arts and Sciences in 2001.



6-axis color adjustment

For special projection material such as high-quality

photographs or artwork, users can adjust the hue, saturation and brightness for six colors: RGBCMY (Red, Green, Blue, Cyan, Magenta, Yellow).



Advanced Features

Edge blending

Edge blending makes it easy to use multi-screen projection and achieve a seamless panoramic image, in which color and brightness match up, even in areas that overlap.



Split Screen

Split Screen⁵ allows you to display content from two inputs simultaneously, side by side, on a single screen with the following features:

- Three layout options, as shown below
- Video and presentation materials displayed simultaneously
- The ability to run video on both screens



Layout Option 1: 50-50% split screen



Layout Option 2: Main image on the left



Layout Option 3: Main image on the right

Multi-PC Projection

EPSON Multi-PC
Collaboration utility allows
you to display four individual
PC screens simultaneously
over the network (wired
or wireless), with another
12 users connected to the
same projector on Standby

mode. You can drag and



drop participants into or out of one of the four quadrants. This feature is a great tool for meetings or classroom projects where multiple users want to present and compare their screens. You can also connect up to four remote projectors at the same time and show the same multi-screen image — another great tool for remote meeting setups.

360-degree projection

The PowerLite Pro Z8350WNL can be rotated 360 degrees in any direction for off-axis positioning flexibility. As a result, it can be used for a wide range of applications, such as projecting on the



ceiling or floor, or as part of a rear-projection system. EPSON technology keeps the projector running without compromising performance or causing overheating.

DICOM simulation mode

DICOM (Digital Imaging and Communication in Medicine) is a standard for handling, storing, printing and transmitting medical imaging information. The projector's DICOM Simulation Mode enables users to reproduce images with an advanced grayscale level that simulates DICOM Part 14. This mode is ideal for viewing grayscale medical images, such as X-rays, for training and educational purposes².







DICOM Simulation Mode

Diverse connectivity

The PowerLite Pro Z8350WNL offers HDMI, BNC and LAN connectivity for easy integration with virtually any system.

Easy Management® with EPSON Monitor

EasyMP® technology makes it easy to monitor and control all networked EPSON projectors. You can use the utility while performing help desk services and proactively manage your projector assets. Remotely power down your projector(s) to extend the lamp life and produce energy savings. The utility also allows you to set up e-mail notifications, verify and change internal settings, and more. The utility is packaged on a CD with the projector and can be used with a PC to check the status of a projector. It is also available online at epson.com





Uninterrupted operation

The PowerLite Pro Z8350WNL boasts a dual lamp system (two 340 W lamps) that eliminates the risk of interruption. If one lamp were to fail, operation would continue, using the other lamp. And, replacements are made easy with tool-free and

unobstructed access to the rear control panel.



Low Cost of Ownership

Schedule function

Using the convenient Schedule function, you can easily control the projector at non-networked venues. The embedded "clock" inside the projector enables it to do scheduled tasks without having the "network stand-by mode" on. This saves energy, as the projector can be turned off when not in use.

Memory function

The Z8350WNL features a Memory function, which allows you to store up to 10 settings in the projector's internal memory. This saves installers valuable time in setting up the projector for various venues and events.

Protect your investment — long-life electrostatic air filter

The PowerLite Pro Z8350WNL filter is designed to protect the optical engine, lamp and electronics from small dust particles that can enter any projector. It has a recommended 10,000-hour filter cleaning schedule. The EPSON electrostatic filter captures particles as small as three microns, due in part to its pleated, expanded design. With one air intake and one exhaust path, the PowerLite Pro Z8350WNL offers an efficient airflow system for optimum cooling of key components and a reduction in dust-related problems. Additionally, it has the capability to send an e-mail notification out through the EPSON Monitor utility when an increase in temperature is detected, due to clogging.




Easy maintenance

Offering convenient access to the lamps and filter, the PowerLite Pro Z8350WNL makes maintenance easier than ever, even if the projector is ceiling mounted. The lamp cover is located on the rear side panel and there are no screws, so the lid can be removed without any special tools. In addition to easy lamp and filter replacements, the Z8350WNL includes features that make it easy to monitor and control. With EasyMP Monitor, users can access advanced status functions over the LAN network.

Quiet, reliable liquid cooling system


Epson's innovative system uses liquid to cool the LCD chips directly. The liquid absorbs the heat and is then cooled by a peltier device, which is then cooled by a fan, thereby keeping the overall optical engine cool. This system design promotes greater reliability and enables stable operation in temperatures up to 122 °F (50 °C). In addition, it offers quiet, unobtrusive operation and allows for off-axis installation orientations.



Easy Installation Tools


Lens shift

EPSON lens shift technology enables outstanding installation flexibility with an incredible range of up to + or - 70% on the vertical axis and up to + or - 20% on the horizontal axis. Users can operate the lens shift functions using the remote control, the projector control panel, or control commands.



Arc correction

Using arc correction, you can adjust each side of a projected image in an arch or barrel-shaped way, making it easier than ever to get a perfectly rectangular image.



Centered lens design

Featuring a centered lens design, the PowerLite Pro Z8350WNL makes installation easy to plan. Positioning the ceiling mount, screen and projector can be performed individually and independent of one another.


Six powered lens options

For great flexibility, the PowerLite Pro Z8350WNL offers a total of six lenses including short, wide, and rear, along with mid- to long-throw lenses that allow users to choose the motorized lens most suited for their environment. A quick release lever allows for a fast, easy lens exchange. (Lens not included)



Test patterns

The PowerLite Pro Z8350WNL also includes six test patterns with precise setup features, including detecting distortion, checking linearity, color reproduction and bleeding, and tone production check.





PowerLite Pro Z8350WNL Features and Benefits

Image Quality

- Powerful combination of brightness and true-to-life color — 8500 lumens color light output, 8500 lumens white light output, WXGA (16:10) resolution and 3LCD, 3-chip technology
- Core technology for added reliability durable LCD chips; innovative cooling system and filter design
- Digital connectivity HDMI with HDCP compliancy and high-grade video processing
- Exceptional color fidelity broad color reproduction covers the DCl color gamut space for viewing movies as film producers intended
- Greater detail with blacker blacks C²Fine technology; up to 5000:1 contrast ratio
- Advanced video quality Super-resolution technology

Advanced Features

- Easier installation 360-degree projection and centered lens design make it easy to install the projector in any setting
- Powered lens motorized zoom, focus, and lens shift, controllable through the remote, RS-232 or IP
- Wide lens shift capabilities and arc correction —
 vertical positioning of up to + or 70%; up to + or 20%
 horizontal; ability to adjust each side of an image in an arch
 or barrel-shaped way
- Split Screen feature project two images (video or still) side-by-side from two different sources simultaneously⁵
- Edge blending multi-screen projection, resulting in a seamless panoramic image
- Demo mode use just one projector to see a side-by-side comparison of an image with Super-resolution turned on and off
- Perfect for auditoriums and lecture hall venues six optional lenses including wide-, rear- and long-throw; designed with a change-out lever for easy installation
- Direct On and Direct Off allows a projector to be powered on/off by use of a wall switch

Low Cost of Ownership

- Protect your investment recommended 10,000-hour filter cleaning schedule ⁶ and easy, side-access filter
- Easy monitor and control capabilities included EPSON Monitor software allows for remote monitor and control of EPSON networked projectors
- Value-added features Quick Corner® for independent image corner control; built-in closed captioning decoder; cable interface cover
- Dual lamps with long lamp life up to 3500-hour lamp life in ECO Mode, up to 2500 hours in Normal Mode⁷



PowerLite® Pro Z8350WNL

Multimedia Projector

Product Name

PowerLite Pro Z8350WNL Lens required

Product Code V11H460920

0 10343 88870 8



Projection System

High-aperture EPSON 3-chip, 3LCD technology

Projection Method

Front/rear/ceiling mount

LCD Driving Method

EPSON Poly-silicon TFT Active Matrix

Pixel Number

1,024,000 pixels x 3LCDs

Color light output¹

8500 lumens

White light output1

8500 lumens (ISO 21118 standard)

Aspect Ratio

Native 16:10, (supports 4:3, 16:9, 5:4)

Native Resolution

Contrast Ratio (Normal, Dynamic Mode)

Up to 5000:1

Color Reproduction

16.7 million colors **Lamp Type**

340 W x 2 UHE

Lamp Life⁷

Up to 3500 hours (ECO Mode) Up to 2500 hours (Normal Mode)

Brightness Uniformity (typical)

Pixel Arrangement

Cross stripe

Projection Lens

Screen Throw Ratio Range

1.71-2.78 (Standard lens)

Size (projected distance) 60'' - 500'

Type

Powered zoom/focus

F-number

1.65 - 2.51 (Standard lens), lens not included

Focal Length

36 mm - 57.35 mm (Standard lens)

Zoom Ratio

Optical zoom 1.0 - 1.61 (Standard lens)

Lens Shift (powered)

Vertical: ±70% Horizontal: ±20%

Keystone Correction

Vertical: -30 degrees to +30 degrees Horizontal: -20 degrees to +20 degrees

Video

DVI: None

Video Standards

Analog: NTSC / NTSC4.43 / PAL / M-PAL / N-PAL /PAL60 / SECAM HDMI: 480i / 576i / 480p / 576p / 720p / 1080i / 1080p

Video Processing

3D Y/C separation, 3D noise reduction, Mosquito noise reduction DCDi — Directional Correlational Deinterlacing Motion-compensated Interlace-Progressive conversion (2:2.3:2 film detection) Super-resolution

Interfaces

Closed captioning

HDMI x 2 Computer: D-sub 15 pin x 1 Video: BNC x 5 Composite Video: BNC x 1 S-Video: Mini DIN x 1 Wired Network: RJ-45 x 1 Wireless Network: Optional Serial: RS-232c x 1 Hardwired Remote Jack x 1 Monitor-Out: D-sub 15 pin x 1 USB Type-A: For wireless only USB Type-B: For service only

Networking

Connectivity

Wired: Integrated 10/100Mbps Wireless: Optional — 802.11b/g/n Wireless Security: WEP, WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES)

Remote Control and Management

EasyMP Monitor

AMX Duet and Device Discovery Crestron Integrated Partner and RoomView Extron IP I ink P.II ink

Other Features

Speaker

None

Audio Output

None

Operating Temperature

32 ° to 122 °F (0 ° to 50 °C) — Normal 32 ° to 104 °F (0 ° to 40 °C) — Above 4900 feet

Other Features (continued)

Power Supply Voltage

EPSON

100 - 240 V ±10%, 50/60 Hz AC

Power Consumption

830 W (ECO Mode) 1050 W (Normal Mode) 15 W standby (Communication on) 0.5 W standby (Communication off)

Fan Noise

35 dB (ECO Mode) 40 dB (Normal Mode)

Security

Kensington®-style lock provision, anchor (metal) bar for security lock or cable, handles attached to body for cable wrap

Dimensions (W x D x H)

Including feet (with standard lens) 21.0" x 28.9" x 8.9'

Excluding feet (with standard lens) 21.0" x 28.9" x 8.0'

Weight

48.4 lb with standard lens

Remote Control

Features

Brightness, contrast, tint, saturation, sharpness, input signal, sync, tracking, position, zoom, focus, lens shift, shutter, ID, source search, split screen

Operating Angle

Front: Right/left ± 60 degrees Upper/lower -45 to +15 degrees

Rear: Right/left ± 30 degrees Upper/lower -45 to +15 degrees

Operating Distance

Support

The EPSON ConnectionSM Pre-sales support

U.S. and Canada 800-463-7766 Internet website www.epson.com

Projectors Programs

Three-year projector limited warranty, 90-day limited lamp warranty, EPSON Road Service Program and PrivateLine® dedicated toll-free support (U.S. and Canada only)

Support (continued)

What's In The Box

I AN -

PowerLite Pro Z8350WNL projector, power cable, computer cable, projector remote control, batteries, cable cover, user manual CD. Quick Setup Sheet, PrivateLine support card, password protection sticker, monitor and control CD

- USB Monitor

> Service RS-232

AC Inlet

Accessory Part Numbers

Standard zoom lens (ELPLS04) V12H004S04 Long-throw zoom lens (ELPLL07) V12H004L07 Middle-throw zoom lens 1 (ELPLM06) V12H004M06 Middle-throw zoom lens 2 (ELPLM07) V12H004M07 Rear projection wide lens (ELPLR04) V12H004R04

Wide zoom lens (ELPLW04) Mount

Flush ceiling mount bracket V12H003B25 Mount bracket with extended pipe V12H003B26 ELPMBP02 False ceiling plate kit

V12H004W04

Other Accessories

Wireless LAN module V12H418P12 Kensington security lock ELPSL01 Hardware remote control cable set V12H005C28 Replacement remote control 1558838 Replacement Lamp

Single (ELPLP72)

V13H010L72 Dual lamp kit (lamp x 2) (ELPLP73) V13H010L73

Replacement Air Filter Set

Replacement air filter set

(ELPAF23) V13H134A23

Packaging Specifications

PowerLite Pro Z8350WNL

Dimensions 23.86" x 34.53" x 12.36" (W x D x H) Weight 55.4 lb

Genuine EPSON Lamp

Single Lamp Dimensions: 5.6" x 8.0" x 6.2" (W x D x H) Weight 1.4 lb **Dual Lamp Dimensions:** 5.6" x 15.9" x 6.2" (W x D x H) Weight 2.7 lb Master Carton

Weight 16.9 lb Units Per Master Carton: 10

Replacement Air Filter Dimensions 3.7" x 12.9" x 1.4" (W x D x H)

Master Carton Dimensions 13.6" x 15.8" x 4.0" (W x D x H) Weight 4.0 lb

Dimensions 16.5" x 28.5" x 7.7" (W x D x H)

Units Per Master Carton: 10

Weight 0.3 lb

Color and white light output will vary depending on mode selected. White light output measured using ISO 21118 standard.

- This projector does not meet the DICOM standard Part 14 and should not be used as a medical diagnostic device.
- 3 Data source: ProjectorCentral.com Jan. 2011. Average of 1038 shipping models for which manufacturers provided lumens and total power data,
- SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.
- The Split Screen feature can only use one digital input source at a time. The other source must be an analog source (PC/Component or Composite video). However, two different analog input sources can
- Recommendation based on normal room conditions. Cleaning requirements may vary depending on use, environment and other conditions. Cleaning intervals may be adjusted to accommodate the environment in which the projector is used.
- Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON, Easy Management, EasyMP, PowerLite and Quick Corner are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and C2Fine are trademarks of Selko Epson Corporation. PrivateLine is a registered trademark and EPSON Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2012 Epson America, Inc. 1/12 CPD-36238 PDF